



WARNING: FAILURE TO FOLLOW THESE RULES MAY RESULT IN SERIOUS INJURY!

Using This Machine With Respect And Caution
Will Considerably Reduce The Risk Of Personal Injury.

SAFETY RULES FOR THE MAGNUM™ FLOORING SHEAR

1. Read and understand this instruction manual before operating the MAGNUM™ Flooring Shear.
2. If you are not thoroughly familiar with the operation of the MAGNUM™ Flooring Shear, obtain advice from a qualified instructor or call 800-406-8998.
3. Stay alert. Do not operate while under the influence of drugs, alcohol, or medication.
4. Always wear safety approved eye protection with side shields (ANSI Z87.1).
5. Keep work area clean and free of debris.
6. Keep children and unauthorized persons away from the MAGNUM™ Flooring Shear and work area.
7. Make sure tool is secure. Operate only on a firm substrate or solid stand.
8. Use the right tool. Do not force the MAGNUM™ Flooring Shear or use it for a job for which it was not designed; use only on approved materials.
9. Keep blade sharp. A dull blade will not perform properly.
10. Always keep hands away from blade while operating or carrying.
11. Do not alter or misuse this tool. The MAGNUM™ Flooring Shear is precision built; modifications not specified in this manual may result in a dangerous condition.
12. Maintain MAGNUM™ Flooring Shear with care. Keep blade sharp and clean. Follow instructions for lubricating and changing accessories.
13. Use only recommended accessories. The use of improper accessories may cause hazards or injury.
14. Never leave the MAGNUM™ Flooring Shear unattended. Secure the handle with the safety lock when not in use.
15. Warning: The dust generated by cutting certain wood, wood fiber, fiber cement, and/or PVC products can be injurious to your health.
16. Bullet Tools does not endorse or warrant inferior "knock off" imitations of our designs. Using these may be dangerous, please contact the manufacturer about any defects with these.

MAKING CUTS




The MAGNUM™ Flooring Shear is operated manually. The two-part extendable handle is grasped by the operator and pushed down to make a cut.



USE EXTREME CAUTION! Blade is very sharp.

CUTTING

1. Unlock safety lock by sliding knob over and down.
 2. Insert material. It is recommended that you **HOLD MATERIAL IN PLACE** until the cut is complete.
- 
- Always keep hands away from blade.**
3. **PUSH HANDLE DOWN TO CUT.** Some effort may be required depending on hardness of material.
 4. **CAUTION: Handle is spring loaded. DO NOT ALLOW HANDLE TO SLAM BACK AFTER MAKING A CUT.**

SAFETY LOCK

For maximum security, the safety lock will automatically reset in the "locked" position unless disengaged. The safety lock can be disengaged by sliding the knob over and down, hooking into slot. (Shown Right)

TRANSPORT

It is important to re-engage lock and secure unextended handle in down position while storing, carrying, or transporting your MAGNUM™ Flooring Shear.

TIP: DOUBLE CUTTING

Most materials (listed on p. 10) shear very well with just one cut. However, some brands of fiber cement siding and other products may require cutting twice to produce a better cut.

Simply make your first cut 1/8" to 1/4" (3 to 6mm) longer than your mark, then go back and make your second cut on your mark. This is very useful to create a cleaner cut when a trim molding or transition cannot be used to cover your cut end.



Locked



Unlocked